

BERGER FOSROC
RANGE OF
PRODUCTS
AND
SOLUTIONS



Concrete Admixtures



Surface Treatments



Grouts & Anchors



Concrete Repairs



Industrial Floorings



Protective Coatings



Joint Sealants



Waterproofing



Adhesives



Cement Grinding Aids

Head Office:

Berger House, House 8, Road 2,
Sector 3, Uttara, Dhaka 1230.

E-mail : enquiry.bangladesh@bergerfosroc.com

Tel.: +88 02 48953665

Website: www.bergerfosroc.com

Brushing Seamless **waterproofing** to your construction



Acrylic polymer based waterproof coating
Brushcrete

Acrylic polymer based waterproof coating

Brushcrete

DESCRIPTION

Single component acrylic polymer modified waterproof coating.

ADVANTAGES



Excellent bond



Seamless coating



Non-toxic



Highly durable

APPLICATIONS



Toilets



Chajjas



Wet areas,
balconies & utilities

COVERAGE

- 0.38 kg/m² in 2 coats
when mixed with 0.75 kg
of cement

SHelf LIFE

- 12 months from the
date of manufacture

PACKAGING

- 5 L, 20 L, 50 L & 200 L packs

APPLICATION INSTRUCTIONS

1 SURFACE PREPARATION




Clean the surface using wire brush
to remove all the dust and
loose particles

2 REPAIR OF SURFACE



Repair the surface defects using
Renderoc range of repair mortars

3 PRE-DAMPENING




Pre-dampen the surface with water
to achieve SSD condition

4 MIXING




Brushcrete shall be mixed with
cement in the ratio of 1:2 using
paddle mixer for 2 to 4 minutes

5 APPLICATION




Apply the first coat of mixed material
and allow it to dry for 5 to 6 hours
before the application of second coat

6 APPLICATION



Apply the second coat of mixed
material once first coat is touch dry

7 CURING



Allow it to air cure for 2 to 6 hours
followed with moist curing
for the next 24 hours