

**BERGER FOSROC**  
RANGE OF  
**PRODUCTS**  
AND  
**SOLUTIONS**



Concrete Admixtures



Surface Treatments



Grouts & Anchors



Concrete Repairs



Industrial Floorings



Protective Coatings



Joint Sealants



Waterproofing



Adhesives



Cement Grinding Aids

**Head Office:**

Berger House, House 8, Road 2,  
Sector 3, Uttara, Dhaka 1230.

E-mail : [enquiry.bangladesh@bergerfosroc.com](mailto:enquiry.bangladesh@bergerfosroc.com)

Tel.: +88 02 48953665

Website: [www.bergerfosroc.com](http://www.bergerfosroc.com)

BF LR/BGD/01.05.2021

# Sealing leakage in seconds



Rapid setting plugging mortar  
for water leakage

## Renderoc Plug



## Rapid setting plugging mortar for water leakage

# Renderoc Plug

### DESCRIPTION

Renderoc Plug is a ready to use powder which requires only addition of clean water to produce a highly consistent, rapid setting mortar which is easy to apply to stop water leakages instantaneously.

### ADVANTAGES



Quick setting - 8 to 10 seconds



Excellent bond to the substrate



Single component - easy to use

### APPLICATIONS

- For the rapid temporary patching and plugging of water from concrete segments, below ground structures, chambers, concrete pipes and basements

### PACKAGING

- 1 kg, 5 kg & 15 kg bags

### SHELF LIFE

- 6 month from the date of manufacture

## APPLICATION INSTRUCTIONS

### 1 MIXING RATIO




Clean water should be added to the powder in the ratio 1 part water: 3 parts Renderoc Plug.

### 2 MIXING PROCESS



Using gloved hands, mix together the water and Renderoc Plug until a lump free ball is produced.

### 3 PLUGGING METHOD




Press the material firmly into the prepared location either by hand or by using a trowel.

### 4 SETTING



If being used to plug running water, the Renderoc Plug should be firmly held in place until initial set has been reached.

### 5 CONTINUE PROCESS



Continue process until water leakage is stopped